



By Appointment to Her Majesty Queen Elizabeth II  
Manufacturers of French Polishes, Solms and Wax Polishes  
John Myland Limited, London

# MYLANDS

ESTABLISHED LONDON 182000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

## SAFETY DATA SHEET

Page: 1

Compilation date: 15/02/2012

Revision date: 09/08/2021

Revision No: 4

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** 2000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

**Product code:** VARIOUS

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Used as a furniture sealer

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** JOHN MYLAND LIMITED  
26 ROTHSCHILD STREET  
WEST NORWOOD  
LONDON  
SE27 0HQ  
UNITED KINGDOM  
**Tel:** 0044 (0) 20 8670 9161  
**Fax:** 0044 (0) 20 8761 5700  
**Email:** sales@mylands.com

#### 1.4. Emergency telephone number

**Emergency tel:** 07831 576 413

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Flam. Liq. 2: H225; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336; -: EUH066

**Most important adverse effects:** Repeated exposure may cause skin dryness or cracking. Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** EUH066: Repeated exposure may cause skin dryness or cracking.  
H225: Highly flammable liquid and vapour.  
H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H336: May cause drowsiness or dizziness.

**Hazard pictograms:** GHS02: Flame

[cont...]

# SAFETY DATA SHEET

2000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

Page: 2

GHS05: Corrosion

GHS07: Exclamation mark



**Signal words:** Danger

**Precautionary statements:** P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P362+P364: Take off contaminated clothing and wash it before reuse.

## 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### PROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	31.161%

##### ETHYL METHYL KETONE

201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	8.670%
-----------	---------	---	--	--------

##### ISOBUTYL ACETATE

203-745-1	110-19-0	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225; -: EUH066	7.450%
-----------	----------	--	-------------------------------	--------

##### 2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	7.230%
-----------	----------	--	--------------------	--------

[cont...]

# SAFETY DATA SHEET

2000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

Page: 3

## ISOBUTANOL

201-148-0	78-83-1	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	6.450%
-----------	---------	---	---	--------

## XYLENE SOLVENT

215-535-7	1330-20-7	-	Skin Irrit. 2: H315; Acute Tox. 4: H312+H332; Flam. Liq. 3: H226	5.460%
-----------	-----------	---	---	--------

## 4-METHYLPENTAN-2-ONE

203-550-1	108-10-1	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; -: EUH066	4.290%
-----------	----------	---	--	--------

## ETHYLBENZENE

202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1.820%
-----------	----------	---	---	--------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

[cont...]

# SAFETY DATA SHEET

2000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

Page: 4

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

PROPAN-2-OL

[cont...]

# SAFETY DATA SHEET

2000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

Page: 5

## Workplace exposure limits:

## Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m <sup>3</sup>	1250 mg/m <sup>3</sup>	-	-

## ETHYL METHYL KETONE

UK	600 mg/m <sup>3</sup>	899 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## ISOBUTYL ACETATE

UK	-63	903 mg/m <sup>3</sup>	-	-
----	-----	-----------------------	---	---

## 2-METHOXY-1-METHYLETHYL ACETATE

UK	274 mg/m <sup>3</sup>	822 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## ISOBUTANOL

UK	154 mg/m <sup>3</sup>	231 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## XYLENE SOLVENT

UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## 4-METHYLPENTAN-2-ONE

UK	208 mg/m <sup>3</sup>	416 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## ETHYLBENZENE

UK	441 mg/m <sup>3</sup>	552 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## DNEL/PNEC Values

DNEL / PNEC No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Cream

**Odour:** Perceptible odour

**Viscosity:** Viscous

**Boiling point/range°C:** 80

**Vapour pressure:** 9.4K Pa

**Flash point°C:** 4

**VOC g/l:** 650

[cont...]

# SAFETY DATA SHEET

2000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

Page: 6

## 9.2. Other information

**Other information:** Reference temperature 20 deg C

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

#### ISOBUTYL ACETATE

ORL	RAT	LD50	13400	mg/kg
ORL	RBT	LD50	4763	mg/kg
SKN	RBT	LD50	>17400	mg/kg

#### 2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
-----	-----	------	-----	-------

[cont...]

## SAFETY DATA SHEET

2000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

Page: 7

ORL	RAT	LD50	8532	mg/kg
-----	-----	------	------	-------

### ISOBUTANOL

IVN	MUS	LD50	417	mg/kg
IVN	RAT	LD50	340	mg/kg
ORL	RAT	LD50	2460	mg/kg

### 4-METHYLPENTAN-2-ONE

IPR	RAT	LD50	400	mg/kg
ORL	MUS	LD50	1900	mg/kg
ORL	RAT	LD50	2080	mg/kg

### ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	mg/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

#### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### Section 12: Ecological information

##### 12.1. Toxicity

**Ecotoxicity values:** No data available.

##### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

##### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

[cont...]

# SAFETY DATA SHEET

2000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

Page: 8

## 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

### 14.2. UN proper shipping name

**Shipping name:** PAINT

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]



## SAFETY DATA SHEET

2000 CELLULOSE SANDING SEALER/MULTIPURPOSE SANDING SEALER/MDF SEALER

Page: 9

### Section 16: Other information

#### Other information

**Other information:** according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312+H332: Harmful in contact with skin or if inhaled

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs through prolonged or repeated exposure.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.